

Floor Mat Installation During PDS

Service Category General

Section Pre-Delivery Service

Market USA

Toyota Supports
 ASE Certification 

Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION
2010	4Runner, Avalon, Camry, Camry HV, Corolla, FJ Cruiser, Highlander, Highlander HV, Land Cruiser, Matrix, Prius, Prius PHV, RAV4, Sequoia, Sienna, Tacoma, Tundra, Venza, Yaris	

TSB REVISION NOTICE

January 21, 2010 Rev1:

- Applicability has been updated to include 2010 Prius PHV model.

Any previous printed versions of this service bulletin should be discarded.

Introduction

2010 model year Toyota vehicles are equipped with driver's side floor mat retaining clips to help ensure the floor mat stays in the correct position. In addition, some models may utilize retaining clips for passenger's side floor mats as well. Attach the driver's side and passenger's side (if applicable) floor mat to the vehicle carpet using the floor mat retaining clips during Pre-Delivery Service (PDS).

Floor Mat Installation During PDS

Introduction (Continued)

CAUTION

- **ONLY** use a floor mat that can be retained using the retaining clips. All OEM Toyota floor mats are specifically designed to fit correctly and be retained using the retaining clips.
- Make sure the driver's side floor mat is properly placed on the vehicle carpet and secured with the retaining clips. If the floor mat is **NOT** properly placed and secured, it could slip and interfere with the movement of the pedals during driving and may cause an accident.
- Verify the operation of the accelerator, brake, and clutch (if equipped) pedals and clearance to the mat.
- **NEVER** install more than one floor mat at a time in the driver's seating position.
- If applicable, any secondary set of floor mats (based upon customer preference, such as the all weather floor mats or other floor mats) **MUST** be placed in the trunk/cargo area with all the packaging material intact. Do **NOT** install the secondary mat on top of the primary floor mat already installed in the driver's seating position.

Warranty Information

OP CODE	DESCRIPTION	TIME	OFF	T1	T2
N/A	Not Applicable to Warranty	-	-	-	-

Installation Procedure

Attach the driver's side and passenger's side (if applicable) floor mat to the vehicle carpet using the clips. Secure the mat by inserting the retaining clips through the grommet holes.

Figure 1. Correct Installation



Figure 2. Incorrect Installation

