



ECO WALKER

Low Rolling-Resistance Passenger Car Tyre

The Eco Walker is a passenger car radial tyre specifically designed to minimise vehicle fuel consumption by providing exceptionally low rolling resistance. The Eco Walker also provides high levels of ride comfort, low tread noise and high levels of wet weather grip.

Features & Benefits

New high-repulsion silica re-inforced tread compound

Exceptionally low rolling resistance & high levels of wet road grip / traction

Lower tyre mass compared to conventional tyres

Minimized rolling resistance

Non-directional, rib / block tread design

Minimized tread noise & irregular wear. Can be rotated to any position

Optimised tread profile

Minimized rolling resistance

Dimensional Data

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES (INCH)
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			
175/65R14 82S	7.5	582	170	266	185	283	5.0	562	5.0 - 6.0
195/65R15 91H	7.7	633	196	289	214	307	5.5	518	5.5 - 7.0
205/55R16 91V	7.7	630	210	290	229	306	6.5	520	5.5 - 7.5
205/60R16 92H	7.7	650	203	298	221	316	6.0	504	5.5 - 7.5
215/60R16 95H	7.8	662	218	303	238	321	6.5	496	6.0 - 7.5
215/55R17 94V	7.8	666	220	307	240	323	7.0	493	6.0 - 7.5