

# MOBILEYE C2-270™

## Our Vision. Your Safety.™



A collision prevention assistant at your service



### Advanced camera alerts you of a possible collision before it happens

#### ☉ Mobileye C2-270 Safety Features

- Daylight Pedestrian Collision Warning, including Bicycle Detection
- Forward Collision Warning, both in Highway and Urban areas, including Motorcycle Detection
- Lane Departure Warning
- Headway Monitoring & Warning

☉ Based on Mobileye's acclaimed vehicle, lane and pedestrian detection technologies

☉ Optional connectivity to various Fleet Management and Telematic systems

☉ High intensity visual indications via LED display, offering

- Vehicle detection indication
- Gauge for headway monitoring
- Color-coded alerts for all warnings

☉ Fits all vehicle types: passenger cars, fleet vehicles, trucks, buses and all other kinds of vehicle

☉ High availability, operating day and night in almost every weather condition

**Mobileye Collision Prevention Systems are functionally effective. They detect reliably and warn the driver when necessary.**

TNO Report, 2009

The Mobileye C2-270™ is a safety solution for collision prevention and mitigation. The system includes a smart camera located on the front windshield inside the vehicle. It utilizes Mobileye's vehicle, lane and pedestrian detection technologies to measure the distance to vehicles, lane markings and pedestrians, providing the driver with life-saving alerts.

The Mobileye C2-270 is never distracted, always looking forward and ready to warn the driver of sudden danger.

#### **Pedestrian Collision Warning (PCW), including Bicycle Detection**

Alerts the driver during daylight with visual and audio warnings of an imminent collision with a pedestrian or cyclist. 71% of pedestrian fatalities occur in urban areas, the Mobileye C2-270 issues a warning up to 2 seconds before a possible collision takes place allowing the driver enough time to react.

#### **Forward Collision Warning (FCW), including Motorcycle Detection**

Alerts the driver to an imminent rear-end collision with the vehicle or motorcycle ahead. Mobileye C2-270 calculates the Time To Collision based on the distance and the relative speed between the two vehicles. Studies showed that 1.5 seconds of early warning can prevent almost 90% of all rear-end collisions. FCW alerts the driver up to 2.7 seconds before a collision occurs, allowing enough time to react.

#### **Lane Departure Warning (LDW)**

Alerts the driver with visual and audio warnings when deviating unintentionally from the driving lane, a situation that may end in a run-off-road crash, rollover,

# MOBILEYE C2-270™

## Our Vision. Your Safety.™



etc. The system measures the distance from the vehicle's wheels to the lane markings on both sides. Studies conducted on Fleets showed a 65% decrease in all lane-departure related crashes using vision-based LDW systems.

### Headway Monitoring & Warning (HMW)

Many drivers overestimate the headway to the vehicle in front, not realizing that, as their speed increases, the effective headway decreases, leaving them insufficient time to react. The headway warnings function provides an audio/visual alert when the headway becomes critically short. The Mobileye C2-270 effectively enhances driving safety by identifying 99.5% of the vehicles ahead on the road.

Pedestrian Collision Warning, which includes Bicycle Detection, alerts the driver when a pedestrian or cyclist enters the vehicle's path in dangerous proximity to the vehicle.



Forward Collision Warning, which includes Motorcycle Detection, alerts up to 2.7 seconds before an anticipated collision with a vehicle ahead.



Lane Departure Warning anticipates an unintentional deviation from the driving lane, and issues a directional alert.



Headway Monitoring assists the driver in keeping a safe driving distance, and issues an alert when the headway distance becomes dangerous.



### System Components

- A windshield-mounted vision sensor unit with a compact High Dynamic Range CMOS (HDRC) camera and Mobileye's SeeQ2® image processing board
- High-quality audio alert buzzer
- User-friendly, high visibility Display and control unit, for visual directional warnings and numerical headway measurement display, with customization options.

### Benefits

- Prevents or mitigates collisions
- Saves lives and prevents injuries
- Reduces collision related costs
- Improves driving habits
- Enhances safe driving
- Provides a tool for driver evaluation and training; helping drivers to develop a keen sense of the vehicle's position within the lane and in relation to other vehicles and pedestrians

### Specifications

- Vision sensor field of view: 40° x 30° (WxH)
- Typical vehicle detection range: 80 meters
- Input Voltage: 12 – 24Vdc
- Operating Temperature: -35C to 80C
- Real-time image processing at 15 FPS running on Mobileye's EyeQ2® vision system on chip
- Adjustable Urban FCW
- Adjustable LDW sensitivity
- Adjustable timing of HMW audio alerts
- Adjustable volume and display brightness
- Automatic notification upon partial or non availability conditions, such as low visibility
- High availability, including in inclement weather
- Data interface options: CANbus, RS485 & J1939
- Vehicle signal inputs: brakes, turn signals, speed, wipers, and high beam

## Mobileye

Our Vision. Your Safety.™

[www.mobileye.com](http://www.mobileye.com)

Mobileye Technologies Limited. All rights reserved 3/2010. Mobileye®, SeeQ2® and EyeQ2® are trademarks of Mobileye Technologies Limited. Specifications are subject to change without notice.